

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Roberts 2072 Premium Linoleum Adhesive
Roberts MSDS Code # 2072C
PRODUCT USES: Trowelable mastic for installing linoleum on floors.

W.H.M.I.S. CLASSIFICATION: NON-CONTROLLED

V.O.C. CONTENT: 0 calculated

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: ROBERTS COMPANY CANADA LTD.
ADDRESS: 2070 Steeles Ave. Bramalea, Ontario L6T 1A7
24 HOUR (CANUTEC) PHONE: (613) 996-6666
DATE REVISED: December 01/06

NAME OF PREPARER: Technical Dept.
INFORMATION PHONE: (905) 791-4444
SOURCES USED: Raw material supplier M.S.D.S.

SECTION II - HAZARDOUS INGREDIENTS INFORMATION

COMPONENT	APPROX. %	UN#	CAS#	LD50	LC50
NO REPORTABLE INGREDIENTS					

SECTION III - PHYSICAL DATA

BOILING POINT: 100° C FREEZING POINT: N/A
VAPOUR DENSITY (AIR=1): Heavier than air
VAPOUR PRESSURE (MM OF MERCURY): As for water.
SOLUBILITY IN WATER: Miscible
APPEARANCE AND ODOUR: Beige, soft buttery paste, very mild resinous odour and ammonia odour.

SPECIFIC GRAVITY (H2O=1): 1.2 pH: 8.5 - 9
EVAPORATION RATE (BUTYL ACETATE=1): Slower
EVAPORATION RATE (ETHYL ACETATE=1): Slower
PERCENT VOLATILE: 39
ODOUR THRESHOLD (PPM): Not available

SECTION IV - FIRE AND EXPLOSION DATA

FLASHPOINT (specify method): None METHOD USED:
FLAMMABLE LIMITS (% BY VOLUME): LOWER: N/A UPPER: N/A IMPACT SENSITIVITY: Insensitive
FIRE EXTINGUISHING MEDIA: Foam, CO2, Dry Chemical AUTO IGNITION TEMP: N/A SENSITIVITY TO STATIC DISCHARGE: Insensitive
SPECIAL FIRE-FIGHTING PROCEDURES: Self-contained breathing apparatus should be worn for fires involving this product. TDG FLAMMABILITY CLASSIFICATION: Not regulated.
UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SECTION V - REACTIVITY DATA

STABILITY: Stable CONDITIONS TO AVOID: Excessive Heat
INCOMPATIBILITY (Materials to avoid): Strong oxidizers and caustics
HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO2, and Hydrocarbons upon combustion.
HAZARDOUS POLYMERIZATION: Will not occur CONDITIONS TO AVOID: None

SECTION VI - TOXICOLOGICAL PROPERTIES

ENTRY ROUTE TABLE

SKIN CONTACT	SKIN ABSORPTION	EYE CONTACT	INHALATION ACUTE	INHALATION CHRONIC	INGESTION
--------------	-----------------	-------------	------------------	--------------------	-----------

EFFECTS OF ACUTE EXPOSURE TO MATERIAL: Product may irritate eyes and skin. Ingestion causes vomiting, diarrhea, depressed respiration. Excessive inhalation of vapors irritating to respiratory tract.

EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: Skin chapping.

LD50 (SPECIFY SPECIES & ROUTE): Not available	LC50 (SPECIFY SPECIES): Not available	EXPOSURE LIMIT: Not available	IRRITANCY: None
SENSITIZING CAPACITY: None	CARCINOGENICITY: None	REPRODUCTIVITY EFFECTS: None	SYNERGISTIC MATERIALS: None known

SECTION VII - PREVENTATIVE MEASURES

RESPIRATORY PROTECTION (SPECIFY TYPE): Not required under anticipated conditions of use.
VENTILATION: Use under well ventilated conditions.
PROTECTIVE GLOVES: Rubber gloves recommended. EYE PROTECTION: Goggles
OTHER PROTECTIVE EQUIPMENT: None required.
SPILL PROCEDURES: Ventilate area. Mechanically collect. Wash area with water. Prevent from entering sewers or waterways. Spilled material may cause slippery conditions. Promptly report significant spills to appropriate authorities. Consult local regulations.
WASTE DISPOSAL METHOD: Destroy by incineration at an approved facility. Dried material only may be landfilled. Consult local regulations.
STORAGE & HANDLING PRECAUTIONS: Keep containers from excessive heat and freezing. Keep out of reach of children.
OTHER PRECAUTIONS: None.

SECTION VIII - FIRST AID MEASURES

EYES: Flush with water for 20 minutes, holding eyelids open. Seek medical attention.
SKIN: Wash with soap and water. Seek medical attention if irritation develops.
INGESTION: Do not induce vomiting. If victim is conscious, give milk or water. Contact physician immediately.
INHALATION: Remove to fresh air upon any onset of discomfort.